



altro

the future is safer with altro

Altro™ K20
contains
recycled material

Altro™ K20 Safety Flooring



Abyss K2001
WR100 / A1M100 / LRV 7



Dolphin K2010
WR86 / A1M86 / LRV 21



Oyster K20215
WR20 / A1M20 / LRV 36



Monsoon K20153
WR81 / A1M81 / LRV 24

Exact Material Match with samples cannot be guaranteed
Eine exakte Übereinstimmung des Materials mit Mustern kann nicht garantiert werden

www.altro.de

Altro™ K20 safety flooring

Flooring Type Belagsart		EN 13845/ EN 13553	Safety flooring Sicherheitsbodenbelag
Classification for use Einsatzbereiche		EN 685	34 & 43 34 & 43
Slip Resistance Rutschsicherheit*		IRRL EN 13845 EN 13893 DIN 51130	> 36 ES1 D5 R11
Thickness Gesamtdicke		EN 428	2 mm
Wear Layer Nutzschicht		EN 429	2 mm
Weight Flächengewicht		EN 430	2,4 kg/m ² 2,4 kg/m ²
Roll Dimensions Rollenabmessungen		EN 426	2 m x 20 m = 40 m ²
Light Fastness Lichtechtheit		EN 20105-802	> 5
Wear Resistance Verschleißverhalten		EN 13845	Group 34/43 Gruppe 34/43
Indentation Rostendruck		EN 433	< 0.10mm
Fire Performance Brandverhalten		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 > 8kW/m ² Pass Klasse Bfl-s1 > 8kW/m ² , bestanden
Chemical Resistance Chemikaleinwirkung**		EN 423	Good beständig
Castor Chair Abrasion Stuhlrollenbeanspruchung		EN 425	Pass geeignet
Under floor heating Fußbodenheizung		EN 12667	Suitable geeignet
Electrical Behaviour Elektrisches Verhalten		EN1815	< 2 kV Antistatic < 2 kV antistatisch
VOC Emissions VOC Emissionen		pEN 15052 Section 01350	Low/Pass gering/geeignet

*For wet areas where bare foot slip resistance is required such as showers and swimming pool surrounds, we recommend the use of Altro Marine T20.
** Caution Ketone/Aromatic Solvents. Please contact Altro for further technical advice regarding staining and chemical resistance.
Contains Biocide.
Installation and Maintenance
All installations in accordance with Altro safety flooring instructions and Local Codes of Practice. Please refer to Altro Cleaning Card for maintenance advice. Failure to install and maintain Altro flooring in accordance with installation instructions can affect its performance and slip resistance. Floors should be protected from other trades and thoroughly cleaned before handover.

Formar

Via Achille Grandi, 26 - 15033 Casale Monferrato (AL)
tel. 0142.455075 - fax 0142.74834
info@formar.it - www.formar.it

Distributor label

For further technical information please visit www.altro.de
Weitere technische Informationen finden Sie auf unserer Website www.altro.de



EN14041
0120
G806/72664

Manufactured by:
Altro Ltd, Works Road
Letchworth, Garden City
SG4 1TW, United Kingdom

K20SC20WAB

Altro is the first safety
flooring manufacturer
to recycle traditional
safety flooring in-house

A+ BRE Generic Green
Guide Rating for Safety
Flooring, full details available
at www.thegreenguide.org.uk

All Altro safety
flooring contains
recycled content