





Altro Marine™ 20 / T20


Like Altro Marine?
Love Altro's shoe
and barefoot ranges



Steam | IPT20807
WR85 / A1M85 / LRV 37



Rainfall | IPT20810
WR135 / A1M135 / LRV 43



Cascade | IPT20809
WR105 / A1M1 / LRV 71




Gull | T20813
WR79 / A1M191 / LRV 46




Marlin | T20811
WR203 / A1M203 / LRV 34




Reef | T20801
WR20 / A1M20 / LRV 41



Shark | IPT20812
WR201 / A1M84 / LRV 24



Tide | IPT20808
WR71 / A1M71 / LRV 21




Seagrass | IPT20814
WR137 / A1M137 / LRV 37

Love Altro's shoe and barefoot ranges Altro Aquarius Altro Pisces



Request your Altro Aquarius™ or Altro Pisces™ sample card now

+44 (0) 1462 707 700 samples@altro.com






Fen | IPT20815
WR242 / A1M242 / LRV 19



Typical Applications

Foot wash areas at swimming pools.

Technical information

Safety requirements	Standard	Value
 Fire behaviour tested in acc. with	EN ISO 9239-1 EN ISO 11925-2	≥ 8kW/m ² Pass
Classified in acc. with	EN 13501-1	B _{f1} -s1
 Slip resistance	EN 13893 EN 13845 Annex C DIN 51130 DIN 51097	DS ESb R10 C
 Sound insulation	EN ISO 140-8	ca. 13 dB

Performance

 Flooring type	EN 13845	Safety flooring
 Thickness	EN ISO 24346	2 mm
 Wear layer	EN ISO 24340	2 mm
 Roll dimensions	EN ISO 24341	2 m x 20 m = 40 m ²
 Weight	EN ISO 23997	2.7 kg/m ²
 Indentation	EN ISO 24343-1	≤ 0.10 mm
 Classification for use	EN ISO 10874	34, 43
 Flexibility	EN ISO 24344	Pass
 Light fastness	EN ISO 105-BO2	≥ 6
 Castor chair abrasion	EN 425	Good
 Wear resistance	EN 13845 Annex D	≤ 10% particles lost over 50000 cycles
 Chemical resistance	EN ISO 26987	Good
 Under floor heating	EN 12524	Suitable
 Electrical behaviours	EN 1815	≤ 2 kV Antistatic
 VOC emissions	Section 01350 / Floorscore	Pass



Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.

CE 07 | Altro Limited, Works Road, Letchworth Garden City, Hertfordshire, SG6 1NW, UK | EN 13845 | DoP-No. 1010 | Reaction to fire Bfl-s1 | Slip Resistance: DS | EN 14041:2008 | 0120 Resilient floor covering to be used within a building



Indication of the level of emissions of volatile substances in the ambient air that are posing a toxic hazard on being inhaled, rated on a scale from A+ (very low emissions) to C (high emissions).



Sustainability



*A+ BRE generic green guide rating for resilient flooring, full details available at www.thegreenguide.org.uk

Installation and Maintenance

Please refer to Altro installation and maintenance instructions. Failure to follow these instructions can affect product performance. Technical information on installation and staining can be found at www.altro.com

Altro Aquarius 20 shades for all wet environments Altro Pisces 16 soft-look shades for a homely feel

Request your Altro Aquarius or Altro Pisces sample card now – ☎ 01462 707 700 ✉ samples@altro.com

Light Reflectance Values measured in accordance with BS 8493:2008. Exact material match with samples cannot be guaranteed.

Codes: WR = weld rod, A1M = mastic, LRV = light reflectance value

 Altro, Altro Marine 20, Altro Aquarius, Altro Pisces and Altro Easyclean Technology are trademarks of Altro Limited.

United Kingdom

☎ +44 (0) 1462 707 700

✉ enquiries@altro.com

Spain

☎ +34 91 549 5230

✉ suelos@altroscandess.com

Australia

☎ +61 3 9764 5666

✉ info@asf.com.au